

WHAT IS CLAIMED IS

5

1. In a mobile communications system
using a code division multiple access method, a call
acceptance controlling apparatus for controlling
acceptance of new calls and handover calls when a
10 communication through a radio channel is performed
between a mobile station in a cell and two or more
radio base stations each forming a cell, the call
acceptance controlling apparatus comprising:

new call acceptance limiting means for
15 restricting acceptance of a new call before any one
of the following events takes place, namely,

an uplink interference amount in each
radio channel from each mobile station that
communicates with a radio base station to the radio
20 base station reaching a predetermined maximum
interference amount of the mobile communications
system,

a downlink total transmission power from
the radio base station to mobile stations reaching a
25 predetermined maximum power level of the mobile
communications system, and

an amount of spread code resources
available in the radio base station reaching null.

30

2. The call acceptance controlling
apparatus as claimed in claim 1, wherein the new
35 call acceptance limiting means restricts acceptance
of a new call before the uplink interference amount
of a radio channel reaches the predetermined maximum

interference amount of the mobile communications system, rejecting the new call to make the new call a lost call, when an uplink interference amount of any radio channel exceeds a first threshold value, comprising:

interference amount measuring means for measuring an interference amount of each uplink radio channel from a mobile station to a radio base station when there is a request for a new call, and

interference amount checking means for determining whether an interference amount of any radio channel measured by the interference amount measuring means is greater than the first threshold value that is defined as being smaller than the predetermined maximum interference amount of the mobile communications system.

3. The call acceptance controlling apparatus as claimed in claim 1, wherein the new call acceptance limiting means restricts acceptance of a new call before the uplink interference amount of a radio channel reaches the predetermined maximum interference amount of the mobile communications system, rejecting the new call to make the new call a lost call, when an uplink interference amount of any radio channel exceeds a second threshold value, comprising:

interference amount estimating means for estimating an interference amount of each uplink radio channel if a request for a new call is accepted, and

interference amount checking means for determining whether an interference amount of any radio channel estimated by the interference amount

estimating means is greater than the second threshold value that is defined as being smaller than the predetermined maximum interference amount of the mobile communications system.

5

4. The call acceptance controlling apparatus as claimed in claim 1, wherein the new call acceptance limiting means restricts acceptance of a new call before the downlink total transmission power reaches the predetermined maximum power level of the mobile communications system, rejecting the new call to make the new call a lost call, when the downlink total transmission power level exceeds a third threshold value, comprising:

total downlink transmission power measuring means for measuring a total transmission power of the radio base station, and

total downlink transmission power checking means for determining whether the total transmission power measured by the total downlink transmission power measuring means is greater than the third threshold value that is defined as being smaller than the predetermined maximum power level of the mobile communications system.

30

5. The call acceptance controlling apparatus as claimed in claim 1, wherein the new call acceptance limiting means restricts acceptance of a new call before the downlink total transmission power reaches the predetermined maximum power level of the mobile communications system, rejecting the

new call to make the new call a lost call, when the total downlink transmission power level exceeds a fourth threshold value, comprising:

- total downlink transmission power
- 5 estimating means for estimating a downlink total transmission power of the radio base station if a requested call is accepted, and

- total downlink transmission power
- checking means for determining whether the downlink
- 10 total transmission power estimated by the total downlink transmission power estimating means is greater than the fourth threshold value that is defined as being smaller than the predetermined maximum power level of the mobile communications
- 15 system.

- 20 6. The call acceptance controlling apparatus as claimed in claim 1, wherein the new call acceptance limiting means restricts acceptance of a new call before all the spread code resources of a radio base station is consumed, rejecting the
- 25 new call to make the new call a lost call, when an amount of the spread code resources available is less than a fifth threshold value, comprising:

- spread code resources measuring means
- for measuring an amount of the spread code resources
- 30 available in the radio base station, and

- spread code resources checking means for determining whether the amount of the spread code resources measured by the spread code resources measuring means is less than the fifth threshold
- 35 value.

7. The call acceptance controlling
apparatus as claimed in claim 2, further comprising
5 first threshold adjustment means for increasing and
decreasing the first threshold value, based on a
lost call ratio of handover calls.

10

8. The call acceptance controlling
apparatus as claimed in claim 3, further comprising
first threshold adjustment means for increasing and
15 decreasing the second threshold value, based on a
lost call ratio of handover calls.

20

9. The call acceptance controlling
apparatus as claimed in claim 4, further comprising
first threshold adjustment means for increasing and
decreasing the third threshold value, based on a
25 lost call ratio of handover calls.

30

10. The call acceptance controlling
apparatus as claimed in claim 5, further comprising
first threshold adjustment means for increasing and
decreasing the fourth threshold value, based on a
lost call ratio of handover calls.

35

10060225-020102

11. The call acceptance controlling apparatus as claimed in claim 6, further comprising first threshold adjustment means for increasing and decreasing the fifth threshold value, based on a lost call ratio of handover calls.

10

12. The call acceptance controlling apparatus as claimed in claim 7, wherein the first threshold adjustment means decreases the first threshold value when the lost call ratio of the handover calls is greater than a first predetermined value, and increases the first threshold value when the lost call ratio of the handover calls is smaller than a second predetermined value that is defined as being smaller than the first predetermined value.

20

13. The call acceptance controlling apparatus as claimed in claim 8, wherein the first threshold adjustment means decreases the second threshold value when the lost call ratio of the handover calls is greater than a first predetermined value, and increases the second threshold value when the lost call ratio of the handover calls is smaller than a second predetermined value that is defined as being smaller than the first predetermined value.

35

14. The call acceptance controlling

apparatus as claimed in claim 9, wherein the first threshold adjustment means decreases the third threshold value when the lost call ratio of the handover calls is greater than a third predetermined value, and increases the third threshold value when the lost call ratio of the handover calls is smaller than a fourth predetermined value that is defined as being smaller than the third predetermined value.

10

15. The call acceptance controlling apparatus as claimed in claim 10, wherein the first threshold adjustment means decreases the fourth threshold value when the lost call ratio of the handover calls is greater than a third predetermined value, and increases the fourth threshold value when the lost call ratio of the handover calls is smaller than a fourth predetermined value that is defined as being smaller than the third predetermined value.

25

16. The call acceptance controlling apparatus as claimed in claim 11, wherein the first threshold adjustment means increases the fifth threshold value when the lost call ratio of the handover calls is greater than a fifth predetermined value, and decreases the fifth threshold value when the lost call ratio of the handover calls is smaller than a sixth predetermined value that is defined as being smaller than the fifth predetermined value.

35

17. The call acceptance controlling apparatus as claimed in claim 2, further comprising:

communication load measuring means for
5 measuring a communication load of a radio base station which forms a cell adjacent to the cell formed by the radio base station concerned, and
second threshold adjustment means for
increasing and decreasing the first threshold value,
10 based on the communication load measured by the communication load measuring means.

15

18. The call acceptance controlling apparatus as claimed in claim 3, further comprising:

communication load measuring means for
measuring a communication load of a radio base
20 station which forms a cell adjacent to the cell formed by the radio base station concerned, and
second threshold adjustment means for
increasing and decreasing the second threshold value,
based on the communication load measured by the
25 communication load measuring means.

30

19. The call acceptance controlling apparatus as claimed in claim 4, further comprising:

communication load measuring means for
measuring a communication load of a radio base
station which forms a cell adjacent to the cell
35 formed by the radio base station concerned, and
second threshold adjustment means for
increasing and decreasing the third threshold value,

based on the communication load measured by the communication load measuring means.

5

20. The call acceptance controlling apparatus as claimed in claim 5, further comprising:
communication load measuring means for
10 measuring a communication load of a radio base station which forms a cell adjacent to the cell formed by the radio base station concerned, and
second threshold adjustment means for increasing and decreasing the fourth threshold value,
15 based on the communication load measured by the communication load measuring means.

20

21. The call acceptance controlling apparatus as claimed in claim 6, further comprising:
communication load measuring means for
measuring a communication load of a radio base
25 station which forms a cell adjacent to the cell formed by the radio base station concerned, and
second threshold adjustment means for increasing and decreasing the fifth threshold value, based on the communication load measured by the
30 communication load measuring means.

35

22. The call acceptance controlling apparatus as claimed in claim 17, wherein the second threshold adjustment means decreases the first

10060225 020102

threshold value when the communication load measured
by the communication load measuring means is greater
than a seventh predetermined value, and increases
the first threshold value when the communication
5 load measured by the communication load measuring
means is smaller than an eighth predetermined value
that is defined as being smaller than the seventh
predetermined value.

10

23. The call acceptance controlling
apparatus as claimed in claim 18, wherein the second
15 threshold adjustment means decreases the second
threshold value when the communication load measured
by the communication load measuring means is greater
than a seventh predetermined value, and increases
the second threshold value when the communication
20 load measured by the communication load measuring
means is smaller than an eighth predetermined value
that is defined as being smaller than the seventh
predetermined value.

25

24. The call acceptance controlling
apparatus as claimed in claim 19, wherein the second
30 threshold adjustment means decreases the third
threshold value when the communication load measured
by the communication load measuring means is greater
than a ninth predetermined value, and increases the
third threshold value when the communication load
35 measured by the communication load measuring means
is smaller than a tenth predetermined value that is
defined as being smaller than the ninth

predetermined value.

5

25. The call acceptance controlling apparatus as claimed in claim 20, wherein the second threshold adjustment means decreases the fourth threshold value when the communication load measured by the communication load measuring means is greater than a ninth predetermined value, and increases the fourth threshold value when the communication load measured by the communication load measuring means is smaller than a tenth predetermined value that is defined as being smaller than the ninth predetermined value.

20

26. The call acceptance controlling apparatus as claimed in claim 21, wherein the second threshold adjustment means increases the fifth threshold value when the communication load measured by the communication load measuring means is greater than an eleventh predetermined value, and decreases the fifth threshold value when the communication load measured by the communication load measuring means is smaller than a twelfth predetermined value that is defined as being smaller than the eleventh predetermined value.

35

27. In a mobile communications system using a code division multiple access method, a call

10660225-020102

acceptance controlling method for controlling
acceptance of new calls and handover calls, when a
communication through a radio channel is performed
between a mobile station in a cell and two or more
5 radio base stations each forming a cell, wherein
acceptance of a new call is limited before any one
of the following events takes place, namely,

an uplink interference amount in each
radio channel from each mobile station that
10 communicates with a radio base station to the radio
base station reaching a predetermined maximum
interference amount of the mobile communications
system,

a downlink total transmission power from
15 the radio base station to mobile stations reaching a
predetermined maximum power level of the mobile
communications system, and

an amount of spread code resources
available in the radio base station reaching null.
20

28. The call acceptance control method
25 as claimed in claim 27, wherein acceptance of a new
call is limited before the uplink interference
amount of a radio channel reaches the predetermined
maximum interference amount of the mobile
communications system, rejecting the new call to
30 make the new call a lost call, when an uplink
interference amount of any radio channel exceeds a
first threshold value, comprising:

an interference amount measuring step
for measuring an interference amount of each uplink
35 radio channel from a mobile station to a radio base
station when there is a request for a new call, and

an interference amount checking step for

determining whether an interference amount of any radio channel measured by the interference amount measuring step is greater than the first threshold value that is defined as being smaller than the predetermined maximum interference amount of the mobile communications system.

10

29. The call acceptance control method as claimed in claim 27, wherein the acceptance of the new call is restricted before the uplink interference amount of the radio channel reaches the predetermined maximum interference amount of the mobile communications system, rejecting the new call to make the new call a lost call, when an uplink interference amount of any radio channel exceeds a second threshold value, comprising:

20 an interference amount estimating step for estimating an interference amount of each uplink radio channel if a request for a new call is accepted, and

25 an interference amount checking step for determining whether an interference amount of any radio channel estimated by the interference amount estimating step is greater than the second threshold value that is defined as being smaller than the predetermined maximum interference amount of the mobile communications system.

35

30. The call acceptance control method as claimed in claim 27, wherein the acceptance of the new call is restricted before the downlink total

transmission power reaches the predetermined maximum power level of the mobile communications system, rejecting the new call to make the new call a lost call, when the downlink total transmission power

5 level exceeds a third threshold value, comprising:

a total downlink transmission power measuring step for measuring a total transmission power of the radio base station, and

10 a total downlink transmission power checking step for determining whether the total transmission power measured by the total downlink transmission power measuring step is greater than the third threshold value that is defined as being smaller than the predetermined maximum power level
15 of the mobile communications system.

20 31. The call acceptance control method as claimed in claim 27, wherein the acceptance of the new call is restricted before the downlink total transmission power reaches the predetermined maximum power level of the mobile communications system,
25 rejecting the new call to make the new call a lost call, when the total downlink transmission power level exceeds a fourth threshold value, comprising:

a total downlink transmission power estimating step for estimating a downlink total transmission power of the radio base station if a
30 requested call is accepted, and

a total downlink transmission power checking step for determining whether the downlink total transmission power estimated by the total
35 downlink transmission power estimating step is greater than the fourth threshold value that is defined as being smaller than the predetermined

10060225.020102

maximum power level of the mobile communications system.

5

32. The call acceptance control method as claimed in claim 27, wherein the acceptance of the new call is restricted before all the spread code resources of a radio base station is consumed, rejecting the new call to make the new call a lost call, when an amount of the spread code resources available is less than a fifth threshold value, comprising:

15 a spread code resources measuring step for measuring an amount of the spread code resources available in the radio base station, and

 a spread code resources checking step for determining whether the amount of the spread code resources measured by the spread code resources measuring step is less than the fifth threshold value.

20

25

33. The call acceptance control method as claimed in claim 28, wherein the first threshold value is increased and decreased, based on a lost call ratio of handover calls.

30

35

34. The call acceptance control method as claimed in claim 29, wherein the second threshold value is increased and decreased, based on a lost

call ratio of handover calls.

5

35. The call acceptance control method as claimed in claim 30, wherein the third threshold value is increased and decreased, based on a lost call ratio of handover calls.

10

36. The call acceptance control method as claimed in claim 31, wherein the fourth threshold value is increased and decreased, based on a lost call ratio of handover calls.

20

37. The call acceptance control method as claimed in claim 32, wherein the fifth threshold value is increased and decreased, based on a lost call ratio of handover calls.

30

38. The call acceptance control method as claimed in claim 33, wherein the first threshold value is decreased when the lost call ratio of the handover calls is greater than a first predetermined value, and the first threshold value is increased when the lost call ratio of the handover calls is smaller than a second predetermined value that is defined as being smaller than the first

35

10060225.000100

predetermined value.

5

39. The call acceptance control method as claimed in claim 34, wherein the second threshold value is decreased when the lost call ratio of the handover calls is greater than a first predetermined value, and the second threshold value is increased when the lost call ratio of the handover calls is smaller than a second predetermined value that is defined as being smaller than the first predetermined value.

15

40. The call acceptance control method as claimed in claim 35, wherein the third threshold value is decreased when the lost call ratio of the handover calls is greater than a third predetermined value, and the third threshold value is increased when the lost call ratio of the handover calls is smaller than a fourth predetermined value that is defined as being smaller than the third predetermined value.

30

41. The call acceptance control method as claimed in claim 36, wherein the fourth threshold value is decreased when the lost call ratio of the handover calls is greater than a third predetermined value, and the fourth threshold value is increased when the lost call ratio of the handover calls is

40060925 020402

smaller than a fourth predetermined value that is defined as being smaller than the third predetermined value.

5

42. The call acceptance control method as claimed in claim 37, wherein the fifth threshold value is increased when the lost call ratio of the handover calls is greater than a fifth predetermined value, and the fifth threshold value is decreased when the lost call ratio of the handover calls is smaller than a sixth predetermined value that is defined as being smaller than the fifth predetermined value.

20

43. The call acceptance control method as claimed in claim 28, further comprising:

a communication load measuring step for measuring a communication load of a radio base station which forms a cell adjacent to the cell formed by the radio base station concerned, and

a threshold adjustment step for increasing and decreasing the first threshold value, based on the communication load measured by the communication load measuring step.

35

44. The call acceptance control method as claimed in claim 29, further comprising:

a communication load measuring step for

measuring a communication load of a radio base station which forms a cell adjacent to the cell formed by the radio base station concerned, and

- a threshold adjustment step for
5 increasing and decreasing the second threshold value, based on the communication load measured by the communication load measuring step.

10

45. The call acceptance control method as claimed in claim 30 further comprising:

- a communication load measuring step for
15 measuring a communication load of a radio base station which forms a cell adjacent to the cell formed by the radio base station concerned, and
a threshold adjustment step for
increasing and decreasing the third threshold value,
20 based on the communication load measured by the communication load measuring step.

25

46. The call acceptance control method as claimed in claim 31, further comprising:

- a communication load measuring step for
measuring a communication load of a radio base
30 station which forms a cell adjacent to the cell formed by the radio base station concerned, and
a threshold adjustment step for
increasing and decreasing the fourth threshold value,
based on the communication load measured by the
35 communication load measuring step.

47. The call acceptance control method as claimed in claim 32, further comprising:

- 5 a communication load measuring step for measuring a communication load of a radio base station which forms a cell adjacent to the cell formed by the radio base station concerned, and
- 10 a threshold adjustment step for increasing and decreasing the fifth threshold value, based on the communication load measured by the communication load measuring step.

15

48. The call acceptance control method as claimed in claim 43, wherein the first threshold value is decreased when the communication load
- 20 measured by the communication load measuring step is greater than a seventh predetermined value, and the first threshold value is increased when the communication load measured by the communication load measuring step is smaller than an eighth
- 25 predetermined value that is defined as being smaller than the seventh predetermined value.

30

49. The call acceptance control method as claimed in claim 44, wherein the second threshold value is decreased when the communication load
- 35 measured by the communication load measuring step is greater than a seventh predetermined value, and the second threshold value is increased when the communication load measured by the communication

load measuring step is smaller than an eighth predetermined value that is defined as being smaller than the seventh predetermined value.

5

10 50. The call acceptance control method as claimed in claim 45, wherein the third threshold value is decreased when the communication load measured by the communication load measuring step is greater than a ninth predetermined value, and the third threshold value is increased when the communication load measured by the communication load measuring step is smaller than a tenth predetermined value that is defined as being smaller than the ninth predetermined value.

20

25 51. The call acceptance control method as claimed in claim 46, wherein the fourth threshold value is decreased when the communication load measured by the communication load measuring step is greater than a ninth predetermined value, and the fourth threshold value is increased when the communication load measured by the communication load measuring step is smaller than a tenth predetermined value that is defined as being smaller than the ninth predetermined value.

35

52. The call acceptance control method as claimed in claim 47, wherein the fifth threshold

5